



Images (Repub.) Description and Claims (90 Kb)

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT
COOPERATION TREATY (PCT)

CORRECTED VERSION

(11) WO 2004/060823

(13) A1

(21) PCT/KR2003/002775

(22) 18 December 2003 (18.12.2003)

(25) Korean

(26) English

(30) 10-2003-0000645

06 January 2003
(06.01.2003)

KR

(43) 22 July 2004 (22.07.2004)

(51)⁷ C03B 33/09

(54) GLASS-PLATE CUTTING MACHINE

(71) RORZE SYSTEMS CORPORATION [KR/KR]; 720 Korim-dong, Yongin,
Kyunggi-do 449-923 (KR).

(72) YOU, Ki-Yong [KR/KR]; 109-1504 Dongsuwon LG Village, 686 Mangpo-

(75) dong, Paldal-gu, Suwon, Kyunggi-do 442-706 (KR). KIM, Choon-Taek
[KR/KR]; 1-305 Poonglim Apt., 498 Wooman 1-dong, Paldal-gu, Suwon,
Kyunggi-do 442-819 (KR). AN, Min-Young [KR/KR]; 605-1205 Samcheon
Jugong Apt., 1-ga, Samcheon-dong, Wansan-gu, Jeonju, Jeonrabuk-do 560-784
(KR). KIM, Mi-Jee [KR/KR]; 205, 275-1 Gugal-ri, Kiheung-eup, Yongin,
Kyunggi-do 449-903 (KR).

(74) HWANG, E-Nam; 507 New Seoul Bldg., 828-8 Yoksam-dong, Kangnam-gu,
Seoul 135-080 (KR).

(81) AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO,
CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM,
HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KZ, LC, LK, LR, LS, LT, LU, LV,
MA, MD, MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT,
RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US,
UZ, VC, VN, YU, ZA, ZM, ZW

(84) ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW),
Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent
(AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU,
MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA,
GN, GQ, GW, ML, MR, NE, SN, TD, TG)

For information on time limits for entry into the national phase please click here

Published

-- with international search report

--

(48) 11 August 2005 (11.08.2005)

(15) see PCT Gazette No. 322005 of 11 August 2005, Section II: page 2/2, drawings, replaced by a new page 2/2

(57) A glass plate cutting machine using a laser beam is provided to solve problems, such as uneven glass section and slanting cutting. By using the glass plate cutting machine of the current invention, the glass plate is irradiated with a first carbon dioxide laser beam of 0.05-2 joule/mm² on a long oval shaped area of 20-200 mm² according to an expected cutting line thereof, and immediately cooled with water, to generate a scribe line, which is then further irradiated with a second carbon dioxide laser beam of 0.1-0.5 joule/mm² on the area of 20-200 mm² thus obtaining a superior glass section.

